



Hot Rolled Coils

Thickness and Width	Lbs. per Sq. Ft.	Grade		
		1010	P&O	A36
16ga. x 36	2.500	x	-	-
16ga. x 42	2.500	x	-	-
16ga. x 48	2.500	x	-	-
16ga. x 60	2.500	x	-	-
14ga. x 36	3.125	x	-	-
14ga. x 40	3.125	x	-	-
14ga. x 42	3.125	x	-	-
14ga. x 48	3.125	x	x	-
14ga. x 50	3.125	x	-	-
14ga. x 58	3.125	x	-	-
14ga. x 60	3.125	x	x	-
14ga. x 72	3.125	x	-	-
13ga. x 48	3.750	x	x	-
13ga. x 60	3.750	-	x	-
12ga. x 36	4.375	x	-	-
12ga. x 42	4.375	x	-	-
12ga. x 48	4.375	x	x	-
12ga. x 60	4.375	x	x	-
12ga. x 72	4.375	x	-	-
11ga. x 36	5.000	x	x	-
11ga. x 48	5.000	x	x	-
11ga. x 60	5.000	x	-	-
10ga. x 36	5.625	x	-	-
10ga. x 42	5.625	x	-	-
10ga. x 48	5.625	x	x	-
10ga. x 60	5.625	x	x	-
10ga. x 72	5.625	x	-	-
10ga. x 84	5.625	x	-	-
8ga. x 36	6.875	x	-	-
8ga. x 48	6.875	x	-	-
8ga. x 52	6.875	x	-	-

Thickness and Width	Lbs. per Sq. Ft.	Grade		
		1010	P&O	A36
7ga. x 36	7.500	x	-	-
7ga. x 38	7.500	x	-	-
7ga. x 42	7.500	x	-	-
7ga. x 48	7.500	x	x	-
7ga. x 54	7.500	x	-	-
7ga. x 60	7.500	x	x	-
7ga. x 72	7.500	x	-	-
3/16 0.177 min x 60	7.660	-	-	x
3/16 0.180 min x 48	7.660	x	x	-
3/16 0.180 min x 54-1/2	7.660	x	-	-
4 ga. 0.221 min x 48	9.375	x	-	-
1/4" x 36	10.210	x	-	-
1/4" x 37	10.210	x	-	-
1/4" x 43	10.210	x	-	-
1/4" x 46	10.210	x	-	-
1/4" x 48	10.210	x	x	x
1/4" x 50	10.210	x	-	-
1/4" x 60	10.210	x	-	x
1/4" x 72	10.210	x	-	x
5/16" x 48	12.760	x	-	-
5/16" x 60	12.760	x	-	x
5/16" x 72	12.760	-	-	x
3/8" x 36	15.320	x	-	-
3/8" x 48	15.320	x	-	x
3/8" x 60	15.320	x	-	x
3/8" x 72	15.320	x	-	x
1/2" x 36	20.420	x	-	-
1/2" x 40	20.420	-	x	-
1/2" x 48	20.420	x	-	x
1/2" x 54	20.420	-	x	-
1/2" x 60	20.420	x	-	x
1/2" x 72	20.420	-	-	x

Eliminate waste by ordering material from coils cut to your exact length requirements.

Please inquire if requirements include items not listed.

Cold Rolled Coils

Thickness and Width	Lbs. per Sq. Ft.
22ga. x 48	1.250
22ga. x 60	1.250
20ga. x 48	1.500
20ga. x 60	1.500
18ga. x 36	2.000
18ga. x 48	2.000
18ga. x 60	2.000
16ga. x 36	2.500
16ga. x 48	2.500
16ga. x 60	2.500
16ga. x 72	2.500
14ga. x 36	3.125
14ga. x 48	3.125
14ga. x 60	3.125
14ga. x 72	3.125
12ga. x 48	4.375
11ga. x 36	5.000
11ga. x 48	5.000

Galvanized Coils

Thickness and Width	Lbs. per Sq. Ft.
30ga. x 36	0.656
28ga. x 36	0.781
26ga. x 36	0.906
26ga. x 48	0.906
26ga. x 60	0.906
24ga. x 36	1.156
24ga. x 48	1.156
24ga. x 60	1.156
22ga. x 36	1.406
22ga. x 48	1.406
22ga. x 60	1.406
20ga. x 36	1.656
20ga. x 48	1.656
20ga. x 60	1.656
18ga. x 36	2.156
18ga. x 48	2.156
18ga. x 60	2.156
16ga. x 36	2.656
16ga. x 48	2.656
16ga. x 60	2.656
14ga. x 36	3.281
14ga. x 48	3.281
14ga. x 60	3.281
12ga. x 36	4.531
12ga. x 48	4.531
12ga. x 60	4.531
11ga. x 48	5.156
10ga. x 36	5.781
10ga. x 48	5.781
10ga. x 60	5.781

Galvannealed Coils

Thickness and Width	Lbs. Per Sq. Ft.	Coating	
		A40	A60
18ga. x 48	2.156	-	x
18ga. x 60	2.156	-	x
16ga. x 48	2.656	x	-
14ga. x 48	3.281	x	-
14ga. x 60	3.281	x	-
12ga. x 60	4.531	x	-
11ga. x 48	5.156	x	-
11ga. x 60	5.156	x	-

Floor Plate Coils

Thickness	Width	Lbs. per Sq. Ft.
14ga.	48	3.75
14ga.	60	3.75
12ga.	48	5.25
12ga.	60	5.25
1/8"	48	6.16
1/8"	60	6.16
1/8"	72	6.16
3/16"	48	8.71
3/16"	60	8.71
3/16"	72	8.71
1/4"	48	11.26
1/4"	60	11.26
3/8"	48	16.37
3/8"	60	16.37

Eliminate waste by ordering material from coils cut to your exact length requirements.

High Strength Coils

Thickness and Width	Lbs. per Sq. Ft.	Grade					
		A607-45	A607-50	A607-60	A715-50	715-50 P&O	A715-80
14ga. x 48	3.125	-	-	-	X	-	-
12ga. x 48	4.375	-	-	-	X	-	-
12ga. x 60	4.375	-	-	-	X	-	-
11ga. x 48	5.000	-	-	-	-	X	-
11ga. x 51	5.000	-	-	-	-	-	X
11ga. x 60	5.000	-	-	-	X	-	-
11ga. x 72	5.000	-	-	-	X	-	-
10ga. x 48	5.625	-	-	-	X	-	X
10ga. x 60	5.625	-	-	-	X	X	X
10ga. x 72	5.625	-	X	-	-	-	X
9ga. 0.142 min x 60	6.250	-	-	-	X	X	-
8ga. 0.154 min x 48	6.875	X	-	-	-	-	-
7ga. 0.1719 min x 48	7.500	-	-	-	X	-	-
7ga. 0.1719 min x 60	7.500	-	-	-	X	-	-
3/16" 0.177 min x 48-1/2	7.660	-	-	-	X	-	-
3/16" 0.177 min x 53	7.660	-	-	X	-	-	-
3/16" 0.177 min x 54	7.660	-	-	-	X	-	-
3/16" 0.180 min x 60	7.660	-	-	-	X	X	X
3/16" 0.180 min x 72	7.660	-	X	-	X	-	-
5ga. 0.209 min x 48	8.750	-	-	-	X	-	-
1/4" 0.240 min x 41	10.210	-	-	X	-	-	-
1/4" 0.240 min x 48	10.210	-	-	-	X	-	-
1/4" 0.240 min x 51	10.210	-	-	X	-	-	-
1/4" 0.240 min x 60	10.210	-	-	-	X	X	-
1/4" 0.240 min x 61	10.210	-	-	-	-	-	X
1/4" 0.240 min x 66	10.210	-	-	X	-	-	-
1/4" 0.240 min x 72	10.210	-	X	-	X	-	-
5/16" x 48	12.760	-	-	-	-	-	X
5/16" x 56-3/4	12.760	-	-	-	-	-	X

Eliminate waste by ordering material from coils cut to your exact length requirements.

Please inquire if requirements include items not listed.